

FUJITSU Image Scanner fi-7140

The essential fi Series scanner with exceptional business performance



■Outstanding paper feeding delivers reliable batch scanning regardless of the document condition

The new scanners allow the user to scan a wide variety of paper thicknesses (27 to 413 g/m^2), as well as plastic cards with the same feeding mechanism inherited from our high-end models. In addition, Paper Protection constantly checks along the whole document length during scanning and automatically stops paper feeding when error occurs to avoid any damage to the document. All in all these deliver the reliable scanning experience expected from Fujitsu.

Reliable Skew Reducer even when scanning a mixed size batch

The fi-7140 automatically detect the document size when scanning a mixed size batch. Furthermore, it is equipped with Skew Reducer to detect the alignment of scanned documents and correct paper skews to minimize missing the edge of the scanned image. Users can rest assured that the result will be good even when scanning documents that are not aligned correctly.



■Compact design for fast scanning right at your desk

The fi-7140 is a compact model that can be placed on the desk, whether for overthe-counter service or for operations in office. It scans at a speed of 40 ppm (A4, color, 200/300 dpi). Simply press the scan button and it will start scanning within a second. Scanning with the fi-7140 will not keep you, or your customers, waiting.



Automatically creates the most suitable high quality image data for **OCR** process

The PaperSteam IP scanner driver, which supports TWAIN/ISIS, saves the inconvenience of fine adjusting the settings for the OCR process. It automatically converts the images into exceptionally clean images, accelerating OCR even when scanning wrinkled or soiled documents or documents with a background pattern.

■Option: Post Imprinter

The optional imprinter unit prints identification markers like dates. alphanumeric codes and symbols on reverse side of the original document. This makes it easier to locate the originals of scanned document when you need to reference them



Post Imprinter (fi-718PR)

■Option: Carrier Sheets

Carrier Sheets allow you to scan documents, photos or clippings larger than A4 size. Documents larger than A4 (such as A3 or B4) or photos and clippings that can be damaged easily can be digitized when using the Carrier Sheets.

*Carrier Sheets (5 sheets per set) can be purchased separately. (The Carrier Sheet should be replaced approximately every 500 scans)



■fi-7140 Technical Specifications

	inical Specificatio			
Description		fi-7140		
Supported operating systems		Windows® 10 (32-bit/64-bit), Windows® 8.1/8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit)		
Scanner type		ADF (Automatic Document Feeder)		
Scanning modes		Simplex / Duplex, Color / Grayscale / Monochrome		
Image sensor ty	/pe	Color CCD (Charge-coupled device) x 2 (front x 1, back x 1)		
Light source		White LED Array x 2 (front x 1, back x 1)		
Multifeed detec	tion	Ultrasonic multi-feed detection sensor x 1, Paper detection sensor		
	Maximum	216 x 355.6 mm (8.5 x 14 in.)		
Document size	Minimum*1	50.8 x 54 mm (2 x 2.13 in.) (Portrait)		
Document Size	Long page scanning (Maximum)*2	216 x 5,588 mm (8.5 x 220 in.)		
Paper weight	Paper	27 to 413 g/m ² (7.2 to 110 lb), A8 size: 127 to 209 g/m ² (34 to 56 lb)		
(Thickness)	Plastic Card	1.4 mm or less*3		
Scanning spec	Color*5			
Scanning speed (A4 Portrait)*4	Grayscale*5	Simplex: 40 ppm (200/300 dpi), Duplex: 80 ipm (200/300 dpi)		
Viviolate	Monochrome*6			
Paper chute capa	acity (A4 Portrait)*7	80 sheets (A4: 80 g/m² or 20 lb)		
Background col	ors	White / Black (Selectable)		
Optical resolution	on	600 dpi		
Output	Color (24-bit)			
resolution*8	Grayscale (8-bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver)*9		
resolution	Monochrome (1-bit)			
	Color	24-bit		
Output format	Grayscale	8-bit		
	Monochrome	1-bit		
Internal video p	rocessing	1,024 levels (10-bit)		
Interface		USB 2.0 / USB 1.1		
Connector shap	e	Туре В		
Image processing functions		Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue / White /Saturation /Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge correction, Vertical streaks reduction, Cropping, Dither, Static threshold		
Power requirem	ents	AC 100 to 240 V ±10%		
Power consumption		Operating: 36 W or less Sleep mode: 1.8 W or less Auto standby (OFF) mode: 0.35 W or less		
Operating environment		Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80% (Non-condensing)		
Dimensions: Width x Depth x Height*10		300 x 170 x 163 mm (11.81 x 6.69 x 6.42 in.)		
Weight		4.2 kg (9.26 lb)		
Included software / drivers		PaperStream IP driver (TWAIN/TWAIN x64/ISIS), Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series*11, Scan to Microsoft SharePoint*11, ABBYY FineReader for ScanSnap™*11, Scanner Central Admin Agent		
Environmental compliance		ENERGY STAR® and RoHS		
Included items		ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM		
*1 The minimum scanning area only applies to using the ADF.				

The minimum scanning area only applies to using the ADF.

Capable of scanning documents that exceed Legal sheets in length. Long page scanning supports documents with a length of up to 5,588 mm (220 in.) when the resolution is set to 200 do or less.

Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feedability.)

Actual scanning speeds are affected by data transmission and software processing times. Indicated speeds are from using IPEC compression.

Maximum capacity varies, depending upon paper weight.

Selectable maximum density may depending upon the length of scanned document.

When scanning at high resolution (over 600 dpi), some limitations apply to the size of the document that could be scanned, depending on system environment.

Excluding the ADF paper chute and Stacker.

The software can be downloaded from the website designated in the Setup DVD-ROM.

■ Options

•	Description	Parts number	Comments
Р	Post Imprinter (fi-718PR)	PA03670-D201	Assists document management by printing numbers, Roman characters and codes on original documents after they have been scanned.
	Carrier Sheet	PA03360-0013	Each package contains 5 carrier sheets. It is recommended that each carrier sheet be replaced after it has been used for 500 scans.
2D	Barcode for PaperStream	PA43404-A433	This option enables the scanner to recognize 2D Barcode. (PDF417, QR code, Data Matrix, Aztec Code)

■Consumables

- Consumation					
	Description	Parts number	Comments		
	Brake Roller	PA03670-0001	Lifetime: Every 200,000 sheets or one year. These rollers separate documents as they are being fed into the scanner.		
	Pick Roller	PA03670-0002	Lifetime: Every 200,000 sheets or one year. These rollers feed documents into the scanner.		
	Print Cartridge	CA00050-0262	Lifetime: 4,000,000 printed characters fi-718PR print head		

■Trademarks

- * ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions.
 * ISIS is a registered trademark of EMC Corporation in the United States.
 * Microsoft, Windows, Windows Server, Windows Vista and SharePoint are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
 * Other company names and product names are the registered trademarks or trademarks of the respective companies.

▲ Safety Precautions

- Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.
- be sure to taletany lead an analyst product and instructed.
 be not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.
 Be sure to limit the use of this product to listed power ratings.



PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Visit the fi Series web site for ordering and purchasing information

http://imagescanner.fujitsu.com